

Indoor Fine Pixel LED

BDTSecureMW7216-E-BL-U



Key Features


- Broadcast grey processing gives more image details
- Superior brightness and color uniformity maintains smooth and complete image quality
- Bezel-free native 1080P, 4K and customized resolution LED video wall system
- High brightness provides vivid images in a range of lighting conditions
- Superior contrast ratio
- Ultra high refresh rate
- Wide view of field: 160°(H)/ 140°(V)
- Low heating and natural heat dissipation mechanism enables fan-less design, no noise
- Support 7*24 working and lower power consumption
- Long service life
- Maintain from the front of the LED making it ideal for space-constrained installations and eliminating the need for rear access space.

Specifications

Model	BDTSecureMW7216-E-BL-U
LED Module	
Module type	Surface mounted trinity LED
Pixel pitch	1.667
Resolution (W×H)	96×108
Dimensions (W×H)	160 mm×180mm
LED Unit	
Dimensions (W×H×D)	640mm×360mm×mm
Modules Component(W×H)	4×2
Resolution(W×H)	384×216
Weight(Kg)	6.95
Screen Area	0.2304 m ²
Pixel Density	360000 pitch/ m ²
Surface evenness	≤0.1
Material	Die-cast Aluminum
Optical	
Single Pixel Brightness Correction	Support
Single Pixel Color Correction	Support
Brightness(nits)	50 to 800 adjustable
Color Temperature(K)	3000 to 10000 adjustable
Viewing Angle	Horizontal 160°, Vertical 140°
Center distance deviation of LED	≤2.5%
Brightness uniformity	≥97%
Color uniformity	≤ ± 0.003 Cx, Cy
Contrast	≥4000:1
Processing Performance	
Grey Level	14 bit
Driving Mode	Constant current driving, 1/27 scan
Frame Frequency	50/60 Hz
Refresh Rate	1920 Hz
Electrical	
Power Supply	110 to 220 VAC
Max Consumption	530 W/ m ²
Average consumption	180 W/ m ²
General	
Maintenance Mode	Front Maintenance

Ingress protection	IP5X
Operation Temperature	-10°C ~ 40 °C
Operating Humidity	8%~85% (No Condensation)
Storage Temperature	-10°C ~ 55°C
Storage Humidity	10%~90% (No Condensation)
Working Hours	≥100,000

Dimensions



“Your Reliable Integrated Video Surveillance Solutions Provider”

Shenzhen Starlink Technology Co.,Ltd

1811, Block A, Zhantao Technology Building, Longhua District, Shenzhen, P.R.China 518131

Email: info@qixingtechnology.com; qixing@qixingtechnology.com

<https://www.qixingtechnology.com>

©2009-2018 Shenzhen Starlink Technology Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.