


## UTP Category 6 Double Jacket Cables

Content of Data Sheet		
Product model	CAB-LC3110B-E-IN	
Product specification	HSYV-6 4×2×0.52	
Test Standard	ISO/IEC11801、TIA-568-C.2、YD/T1019	
Conductor	Material	OFC(Oxygen free copper)
	AWG	24
	Nom.O.D.(mm)	0.52±0.03 mm
	DC resistance	≤95 Ω/km
Insulation	Material	HDPE
	Thickness	0.2±0.02 mm
	Diameter	0.93±0.05 mm
	Color	Blue/White- Blue Orange/White-Orange
Pitch	Offset pitch	≤20 mm
	Cable pitch	≤120 mm
Sheath	Material(IN Jacket)	PVC(complies RoHS/REACH)
	Material(OUT Jacket)	LDPE
	External O.D.	6.9±0.3 mm
	Color	Black
	Tensile strength(PVC)	>13.5 Mpa
	Thickness	0.55±0.05 mm
Surface Printing	Letter height	3.0±0.3 mm
	Color	White
	Print error & Space	1±0.005 m



	Case number	Yes	
Packing	Wooden shaft		
Packing length	305±1m		
Rip-cord	Yes	Crossing backbone	Yes
Ambient temperature	-20°C~60°C		

“Your Reliable Integrated Video Surveillance Solutions Provider”

**Shenzhen Starlink Technology Co.,Ltd**

1811, Block A, Zhantao Technology Building, Longhua District, Shenzhen, P.R.China 518131

Email: info@qixingtechnology.com; qixing@qixingtechnology.com

<https://www.qixingtechnology.com>

©2009-2018 Shenzhen Starlink Technology Co.,Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.